

Hazardous, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Flowshield ESD SL Base A

Recommended use: No Information

Supplier: Tremco CPG Australia Pty Ltd

ABN: 25 000 024 064

Street Address: 12/4 Southridge Street

Eastern Creek NSW 2766

Telephone: 02 9638 2755 **Facsimile:** 02 9638 2955

Emergency Telephone number: 02 9037 2994

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.







Signal Word

Danger

Hazard Classifications

Acute Toxicity - Inhalation - Category 4 Skin Corrosion/Irritation - Category 2 Eye Damage/Irritation - Category 2A Sensitisation - Skin - Category 1

Specific Target Organ Toxicity (Repeated Exposure) - Category 1

Chronic Hazard to the Aquatic Environment - Category 2

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life.

Prevention Precautionary Statements

P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P260	Do not breathe dust, fume, gas, mist, vapours or spray.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing including eye/face protection.

Response Precautionary Statements

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270



P101 If medical advice is needed, have product container or label at hand.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

Poison Schedule:

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 9

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

- (a) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or
- (b) IBCs.

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Quartz (SiO2) Bisphenol-A epoxy resin Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives Benzyl alcohol Ingredients determined to be Non-Hazardous	14808-60-7 25068-38-6 68609-97-2 100-51-6	25-50 % 25-50 % 2.5-10 % 2.5-10 % Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Move to fresh air. Consult a physician after significant exposure.

Skin Contact: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

Ingestion: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270 Issued: 2022-05-11 Version: 1 Page 2 of 8



PPE for First Aiders: Wear safety shoes, overalls, gloves, apron, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. When symptoms persist or in all cases of doubt seek medical advice. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3Z

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

LARGE SPILLS

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Dangerous Goods - Initial Emergency Response Guide No: 47

7. HANDLING AND STORAGE

Handling: Ensure adequate ventilation. Use personal protective equipment. Use only in area provided with appropriate exhaust ventilation.

Storage: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

This material is classified as a Class 9 Miscellaneous Dangerous Good as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270

Issued: 2022-05-11 Version: 1 Page 3 of 8



	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Quartz (respirable dust)	-	0.05	-	-	Carc. 1A
Silica Crystalline - Quartz (respirable dust)	-	0.05	-	-	Carc. 1A

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, APRON, CHEMICAL GOGGLES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, apron, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

RECOMMENDATIONS FOR CONSUMER USE:

RESPIRATORY PROTECTION: Respirator with a vapor filter.EYE PROTECTION: Tightly fitting safety goggles.HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeabilityand break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing.Remove and wash contaminated clothing before re-use. Rubber or plastic apron.

Hygiene measures: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Colour: colour on label Odour: Not determined

Solubility: Not determined

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270 Issued: 2022-05-11 Version: 1 Page 4 of 8



Solubility in water: Not determined

Specific Gravity: 0.114

Density: Not determined Relative Vapour Density (air=1): Approx 2.65 Vapour Pressure (20 °C): Not determined

Flash Point (°C):

Flammability Limits (%):

Autoignition Temperature (°C):

Melting Point/Range (°C):

Pour Point/Range (°C):

Boiling Point/Range (°C):

Not determined
Not determined
136 - N.D

Decomposition Point (°C): Not determined Sublimation Point (°C): Not determined **Dropping Point (°C):** Not determined pH: Not determined Viscosity: Not determined **Surface Tension:** Not determined Evaporation Rate (n-Butyl acetate=1): Not determined **Partition Coefficient:** Not determined

Total VOC (g/Litre): 0

Odour Threshold:

Explosive properties:

Oxidising properties:

Volatile by Volume:

Molecular Formula:

Molecular Weight:

not determined

Not determined

Not determined

Not determined

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: No decomposition if stored and applied as directed. Stable under normal conditions.

Conditions to avoid: No Information

Incompatible materials: Strong oxidizing agents. Acids and bases. Amines.

Hazardous decomposition products: Hazardous polymerisation does not occur.

Hazardous reactions: No reactivity hazards known under normal storage and use conditions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Harmful if inhaled. No information available

Skin contact: No information available A skin sensitiser. Repeated or prolonged skin contact may lead to

allergic contact dermatitis.

Ingestion: No information available

Eye contact: No information available

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270

Issued: 2022-05-11 Version: 1 Page 5 of 8



Acute toxicity

Inhalation: This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): $10.0 < LC_{50} \le 20.0$ mg/L for vapours or $1.0 < LC_{50} \le 5.0$ mg/L for dust and mist.

Benzly Alcohol LC50 (Rat): >4178 mg/m3

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Benzyl Alcohol LD50 (Rabbit): 2000 mg/kg Bisphenol A LD50 (Rat): >2000 mg/kg

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Bisphenol A LD50 (Rat): >2000 mg/kg Oxirane LD50 (Rat): 17100 mg/kg Benzyl Alcohol LD50 (Rat): 1620 mg/kg

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as a Category 1 Hazard.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information

Benzyl alcohol 48hr EC50 (Daphnia magna): 230 mg/l

Benzyl alcohol 72hr IC50 (algae): 700 mg/l Benzyl alcohol 96hr LC50 (fish): 460 mg/l

Long-term aquatic hazard: No information

Ecotoxicity: No information

Persistence and degradability: No information

Bioaccumulative potential: No information

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270

Issued: 2022-05-11 Version: 1 Page 6 of 8

Mobility: No information



Page 7 of 8

13. DISPOSAL CONSIDERATIONS

If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

- (c) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or
- (d) IBCs.



UN No: 3082

Dangerous Goods Class: 9

Packing Group: III

Hazchem Code: •3Z

Emergency Response Guide No: 47

Limited Quantities 5 L

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1). Note 1: Materials that are fire risks are incompatible with oxidising agents (Class 5.1) or organic peroxides (Class 5.2). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 3082
Dangerous Goods Class: 9
Packing Group: III

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

AIR TRANSPORT

Issued: 2022-05-11

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270

Version: 1



Page 8 of 8



UN No: 3082 **Dangerous Goods Class:** 9 **Packing Group:** Ш

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): .

16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: Flowshield ESD SL Base A Reference No: A1AAU610270 Issued: 2022-05-11

Version: 1