

Safety Data Sheet

Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Flowfresh Coating Satin- Base A**

Recommended use: No Information

Supplier: Tremco CPG Australia Pty Ltd
ABN: 25 000 024 064
Street Address: 12/4 Southridge Street
Eastern Creek NSW 2766
Telephone: 02 9638 2755
Facsimile: 02 9638 2955

Emergency Telephone number: **02 9037 2994**

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.



Signal Word

Warning

Hazard Classification

Sensitisation - Skin - Category 1

Hazard Statement

H317 May cause an allergic skin reaction.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing dust, fume, gas, mist, vapours or spray..
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing including eye/face protection.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P321 Specific treatment (see on product label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule:

Safety Data Sheet



DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

| CHEMICAL ENTITY | CAS NO | PROPORTION |
|--|------------|------------|
| 1,2-Ethanediol | 107-21-1 | 2.5-10 % |
| Solvent naphtha, petroleum, light aromatic | 64742-95-6 | 0.1-1.0 % |
| Dipentene | 138-86-3 | 0.1-1.0 % |
| Cyclohexene, 1-methyl-4-(1-methylethylidene)- | 586-62-9 | 0.1-1.0 % |
| Formaldehyde | 50-00-0 | <0.1 % |
| mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2hisothiazol-3-one [EC no. 220-239-6] (3:1) | 55965-84-9 | <0.1 % |
| Ingredients determined to be Non-Hazardous | | Balance |
| | | <hr/> 100% |

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Move to fresh air. Consult a physician after significant exposure.

Skin Contact: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

Ingestion: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

PPE for First Aiders: Wear overalls, gloves, apron, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Safety Data Sheet



Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material.

LARGE SPILLS

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Wear personal protective equipment. Do not breathe vapours or spray mist.

Storage: CONDITIONS TO AVOID: Direct sources of heat. Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

| | TWA | | STEL | | NOTICES |
|-------------------------------|-----|-------|------|-------|---------|
| | ppm | mg/m3 | ppm | mg/m3 | |
| Ethylene glycol (particulate) | - | 10 | - | - | Sk |
| Ethylene glycol (vapour) | 20 | 52 | 40 | 104 | Sk |
| Formaldehyde | 1 | 1.2 | 2 | 2.5 | Sen |

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

'Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during

Safety Data Sheet



product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: OVERALLS, GLOVES, APRON, CHEMICAL GOGGLES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear overalls, gloves, apron, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

RECOMMENDATIONS FOR CONSUMER USE:

RESPIRATORY PROTECTION: Respirator with a vapor filter.**EYE PROTECTION:** Tightly fitting safety goggles.**HAND PROTECTION:** Impervious gloves, Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron.**OTHER PROTECTIVE EQUIPMENT:** No Information**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Hygiene measures: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|----------------|
| Base Units: | Kilogram |
| Form: | Liquid |
| Colour: | Amber |
| Odour: | slight |
| Solubility: | Not determined |
| Solubility in water: | Not determine |
| Specific Gravity: | 0.090 |
| Density: | ~1.03 |
| Relative Vapour Density (air=1): | Not determined |
| Vapour Pressure (20 °C): | Not determined |
| Flash Point (°C): | >100°C |
| Flammability Limits (%): | Not determined |
| Autoignition Temperature (°C): | Not determined |
| Melting Point/Range (°C): | Not determined |
| Pour Point/Range (°C): | Not determined |
| Boiling Point/Range (°C): | 156 - N.D. |
| Decomposition Point (°C): | Not determined |
| Sublimation Point (°C): | Not determined |
| Dropping Point (°C): | Not determined |
| pH: | Not determined |
| Viscosity: | Not Determined |
| Surface Tension: | Not Determined |
| Evaporation Rate (n-Butyl acetate=1): | Not Determined |
| Partition Coefficient: | Not Determined |
| Total VOC (g/Litre): | 0 |

Product Name: Flowfresh Coating Satin- Base A

Reference No: B1AMY600107

Issued: 2022-03-23

Version: 2

Page 4 of 7

Safety Data Sheet



| | |
|------------------------------|----------------|
| Odour Threshold: | Not Determined |
| Explosive properties: | Not determine |
| Oxidising properties: | Not determine |
| % Volatile by Volume: | Not determine |
| Molecular Formula: | Not Determined |
| Molecular Weight: | Not Determined |

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: Stable under recommended storage conditions

Conditions to avoid: Direct sources of heat.

Incompatible materials: No Information

Hazardous decomposition products: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Hazardous reactions: No reactivity hazards known under normal storage and use conditions. Hazardous polymerisation does not occur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: No information available

Skin contact: No information available A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: No information available

Eye contact: No information available

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): LC₅₀ > 20.0 mg/L for vapours or LC₅₀ > 5.0 mg/L for dust and mist.

Solvent naphtha (petroleum), light arom. LC₅₀ (Rat): 3670 ppm/8 hours (Method: Inhalation)

Formaldehyde LC₅₀ (Rat): 250 - 590 mg/cu m (Method: Vapor)

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [EC no. 220-239-6] (3:1) LC₅₀ (Rat): 0.33 mg/L (Method: Vapour - (inh/4h/rat - dust))

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): LD₅₀ > 2,000 mg/Kg bw

mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [EC no. 220-239-6] (3:1) LD₅₀ (Rabbit): 87.12 mg/kg (Method: Dermal)

Solvent naphtha (petroleum), light arom. LD₅₀ (Rat): >2000 mg/kg (Method: Dermal)

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity

Safety Data Sheet



estimate (based on ingredients): LD₅₀ > 2,000 mg/Kg bw

Solvent naphtha (petroleum), light arom. LD50 (Rat): 4700 mg/kg (Method: Oral)

Formaldehyde LD50 (Rat): 100 mg/kg, (Method: Oral)

mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [EC no. 220-239-6] (3:1) LD50 (Rat): 64 mg/kg (Method: Oral)

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as not a specific hazard to target organs by repeat exposure.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: H400 Very toxic to aquatic life.

Solvent naphtha (petroleum), light arom 48hr EC50 (Daphnia magna): >1 - 10 mg/l

Solvent naphtha (petroleum), light arom 72hr IC50 (algae): >1 - 10 mg/l

Solvent naphtha (petroleum), light arom. 96hr LC50 (fish): >10-100 mg/l

mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [EC no. 220-239-6] (3:1) 96hr LC50 (rainbow trout): 0.19 mg/L (Oncorhynchus mykiss)

Long-term aquatic hazard: H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Ecotoxicity: No information

Persistence and degradability: No information

Bioaccumulative potential: No information

Mobility: No information

13. DISPOSAL CONSIDERATIONS

Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Safety Data Sheet



14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): .

16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.